

- Overall, it can be concluded that the dual fuel operations of dual fuel with B 25 + AG 30% gives improved engine performance and lower tail pipe emissions compared with other Acetylene gas flow rates.

126, 297-301.

REFERENCES

[1] Deshmukh, Samir J., Bhuyar, Lalit B., Thakre, Shashank B. 2008. Investigation on Performance and Emission Characteristics of CI Engine Fuelled with Producer Gas and Esters of Hingan (Balanites) Oil in Dual Fuel Mode.

[2] Hassan, S., MohdNor, F., Zainal, Z.A., Miskam, M.A. 2011. Performance and emission characteristics of supercharged Biomass producer gas-diesel dual fuel engine.

[3] Mathur, M.L., Sharma, R.P. 2006. Internal combustion engine, Dhanpatrai publication, p. 738.

[4] Singh, R.N., Singh, S.P., Pathak, B.S. 2007. Investigations on operation of CI engine using producer gas and rice bran oil in mixed fuel mode. *Renewable Energy*, 32, 1565-1580.

[5] Shrivastava, V., Jha, A.K., Wamankar, A.K., Murugan, S. 2013. Performance and Emission studies of a CI Engine coupled with gasifier running in dual fuel mode. *Procedia Engineering*, 51, pp 600-608.

[6] Lin, C.L., Wey, M.L., You, S.D. 2002. The effect of particle size distribution on minimum fluidization velocity at high temperature. *power technology*,

[7] Tiwari, G.N., Ghosal, M.K. 2007. *Fundamentals of Renewable Energy Sources: Basic Principles and Applications*, Narosa Publishing House, New Delhi.

[8] Stassen, H.E.M., Knoef, H.A.M. 1993. *Small scale gasification systems*, The Netherlands: Biomass Technology Group, University of Twente.

[9] Bridgwater, A.V., Evans, G.D. 2012. *An Assessment of Thermo chemical Conversion Systems for Processing Biomass and Refuse*. Harwell Laboratory, Energy Technology Support Unit: ETSU B/T1/00207/REP.

[10] Juan, J., Aranda-Almsnsa, H.G., Bula, A. 2010. Gasification of biomass wastes in an entrained flow bio diesel effect of the particle size and the residence time, 91 (6), 681-692.

[11] Das, D.K., Dash, S.P., Ghosal, M.K. 2011. Performance Study of a Diesel Engine by using producer gas from Selected Agricultural Residues on Dual-Fuel Mode of Diesel-cum-Producer gas.

[12] Roy, M.M., Tomita, E., Kawahara, N., Harad, Y., Sakane, A. 2009. Performance and emission comparison of supercharged dual-fuel engine fuelled by producer gases with varying hydrogen content.

[13] Volli, V., Singh, R.K. 2012. Production of bio-oil from de-oiled cakes by thermal pyrolysis, NIT Rourkela, India.

[14] McKendry, P. 2002. Energy production from biomass (part 3): gasification technologies. *Journal of Bio resource Technology*, 83, 55-63.

